

# Surge Secure Dual Euro Socket Power Protector (250V / 16A max. load)



Product Code: FBWPP2  
Barcode: 6002844068257

**High Surge Protection**  
**R30 000**  
**Warranty**

Repair or Replace warranty terms and conditions apply.



PROTECTS UP TO  
**2**  
APPLIANCES ONLY  
MAX CONNECTED  
LOAD: 3680W

- 2 Year Warranty claim period
- Conforms to the highest South African standards
- Surge Safe Adaptor has a built-in mains tester
- Protects 2 appliances only with Euro socket
- Manufactured from self-extinguishing material

## Mains Checker

Surge Secure Dual Euro Socket Power Protector Plug has a built-in 3 LED light mains checker, refer to the diagram below to understand the lighting patterns.

If all the Surge Safe Plug indicator lights are **OFF** when the wall socket switch is **OFF**, then switch **ON** the wall socket switch and the following applies:-



Correct.



No earth.



No live.



Live and neutral reversed.

If any of the Surge Safe Plug lights are **ON** when the wall socket switch is **OFF**, then switch **ON** the wall socket switch and the following applies:



Live and earth reversed.



Faulty neutral.



Live and neutral reversed.



Faulty earth.



Overload circuit, fused wires.

## Surge Safe Plug

Don't risk losing your valuable equipment through a surge, protect it with the Surge Safe Plug.

## What is a surge?

A surge is an abnormal but temporary high voltage on the electrical mains caused by non-direct lightning strikes or from noise possibly produced by the use of heavy duty appliances, heavy duty machinery or large power tools.

- This product does not protect against direct lightning strikes.

For R30 000 warranty to be valid, enclosed warranty form needs to be completed and submitted to Ellies (Pty) Ltd with all other required documents within 30 days from date of purchase.



**FIRE RESISTANT**  
MANUFACTURED WITH  
FLAME RETARDANT MATERIALS

## PACKAGE CONTENTS

- 1 x FBWPP2
- 1 x Surge warranty form  
(This form needs to be filled in by the customer in full, in order for claiming purposes)

## TECHNICAL INFORMATION

### Specifications:

Surge Level	
Max total combined surge current (Amps)	<b>18 000 - 24 000</b>
Max total combined surge energy (Joules)	<b>500 - 700</b>
Protection component response time (nSec)	<b>&lt; 25</b>
<b>Max connected load: 3680W</b>	

## PACKAGING DIMENSIONS

	Weight (kg)	Height (mm)	Width (mm)	Depth (mm)
Package	-	102	69	55.5

www.ellies.co.za

